



Red Lead Powder

A bright orange powder with strong preservative properties. When mixed with linseed-oil putty it make 'red lead putty' for use as stopping in seams below the waterline on wooden craft.

An appropriate ratio of 16 parts putty to 1 part red lead powder is about the right proportions, with linseed oil added to modify the mixture to the required consistency.

Part No. 5049/00/001 1 kg. tub

Part No. 5049/00/025 25 kg. bag



White Lead Paste

A stiff white paste used for luting joints in timber construction and bedding fittings. Linseed-oil or putty can be added to modify the consistency. The light colour makes it the preferred stopping above the waterline, where white, or other light shades of paint, may be used.

Part No. 5048/00/003 3 kg. tub

Part No. 5048/00/025 25 kg. drum



Stockholm Tar

A strongly preservative thick liquid used to preserve natural cordage and timber. Traditionally used to coat servings on rigging and is the substance added to oakum to stop it rotting. Worth having for the wonderful smell alone.

Part No. 2809/00/01 1 kg tub

Part No. 2809/00/02 2.25 kg tub

Part No. 2809/00/25 25 kg drum



Brass & Copper Cleaner

The strong answer for heavily oxidised brass, copper or bronze fittings. Just apply with a soft cloth and rub until all traces of oxidation are removed and your fittings are like new.

Part No. 5059/00/0500 500ml bottle



Brass & Copper Polish

After cleaning your hardware, enhance its appearance with this water based, low odour polish. Regular use will reduce tarnishing.

Part No. 5060/00/0125 125 ml bottle