Rigging & Sail Handling



Mast Bands

Cast in gunmetal or galvanised iron, they are available with either two or four eyes.





Gunmetal	Galvanised	No of	Inte	Internal dia.	
		Eyes			
3416/GM/038	-	2	1½"	38mm	
3416/GM/050	3416/GA/050	2	2"	50mm	
3416/GM/062	3416/GA/062	2	21/2"	62mm	
3416/GM/075	3416/GA/075	2	3"	75mm	
3416/GM/087	3416/GA/087	2	31/2"	87mm	
3416/GM/100	3416/GA/100	2	4"	100mm	
3418/GM/050	3418/GA/050	4	2"	50mm	
3418/GM/062	3418/GA/062	4	21/2"	62mm	
3418/GM/075	3418/GA/075	4	3"	75mm	
3418/GM/087	3418/GA/087	4	31/2"	87mm	
3418/GM/100	3418/GA/100	4	4"	100mm	

Sliding Gooseneck



This all brass dinghy fitting consists of a spike on a gooseneck with tangs and thumb screw for adjustment. Supplied with 12" (300mm) of brass internal track, size %" (16mm).

Part No. 3401/BR

Halfband & Spike

Available in gunmetal or galvanised iron.



Gunmetal	Galvanised	Jaw width	
3402/GM/050	-	2"	50mm
3402/GM/062	3402/GA/062	21/2"	62mm
3402/GM/075	3402/GA/075	3"	75mm
3402/GM/087	3402/GA/087	3½"	87mm

Tack







Boom Fittings

Tack and clew fittings cast in gunmetal. The clew fitting has a double swivel tang, and the tack has a square hole for use with roller reefing.

Part No	Description	Diameter	
9446/GM/T/050	Tack Boom End Fitting	2"	50mm
9446/GM/C/050	Clew Boom End Fitting	2"	50mm



Bronze Reefing Claw

Cast in aluminium bronze, which is a very tough alloy, this product is particularly suited to its purpose, being very stiff and strong yet without excessive bulk.

Part No	Inside Diameter	
9447/AB/100	4"	100 mm
9447/AB/125	5"	125 mm



Parrel Beads

Turned from Ash and treated with Linseed Oil.

Part No.	Length x Diameter		Bore
0924/00/022	7⁄8" x 7∕8"	22 x 22mm	6mm
0924/00/035	13/8" x 11/8"	35 x 28mm	8mm
0924/00/044	1¾" x 1¾"	44 x 35mm	10mm
0924/00/050	2"x 15/8"	50 x 42mm	12mm
0924/00/070	2 ³ / ₄ " x 2 ³ / ₁₆ "	70 x 55mm	18mm