


Rigging & Sail Handling



Galvanised Rigging Screw

Closed body fork and fork rigging screw with lock nuts. Hot dipped galvanised.



Galvanised	Thread Size	Length of Body
1371/GA/06/100	¼" 6mm	4" 100mm
1371/GA/08/112	⅜" 8mm	4½" 112mm
1371/GA/10/125	½" 10mm	5" 125mm
1371/GA/12/200	⅝" 12mm	8" 200mm
1371/GA/16/225	¾" 16mm	9" 225mm

Ships Pattern Rigging Screw

Galvanised tubular fork & eye rigging screw with metric threads. Shackle and thimble optional extras. Available tested and stamped with certificate to special order.



Galvanised	Thread Size	Body Length	Proof Load kgs
1370/GA/10/150	⅜" 10mm	6" 152mm	400
1370/GA/12/225	½" 12mm	9" 229mm	1000
1370/GA/16/225	⅝" 16mm	9" 229mm	1400
1370/GA/19/225	¾" 20mm	9" 229mm	2000

Larger sizes available to order.



Pelican Hook

Cast in gunmetal and polished. 4" (100mm) long overall. Part No. 1390/GM

Belaying Pins

Available in gunmetal, brass, galvanised iron and turned ash.



Gunmetal	Brass	Galvanised	O.A. Length	Stem Length	Stem Diameter
-	1634/BR/156	1634/GA/156	6½" 158mm	3¾" 95mm	⅜" 10mm
-	1634/BR/187	1634/GA/187	7½" 190mm	4½" 114mm	½" 12mm
1634/GM/231	-	1634/GA/231	8¾" 222mm	5" 125mm	⅝" 16mm



Ash	O.A. Length	Stem Length	Stem Diameter
1636/AH/280/25	11" 280mm	6½" 165mm	⅝" 24mm
1636/AH/360/29	14½" 365mm	8¾" 223mm	1⅝" 29mm
1636/AH/500/32	20" 500mm	12" 305mm	1¼" 32mm

Galvanised Heart Thimbles



Galvanised	Rope Diameter	Galvanised	Rope Diameter
1190/GA/003	3	1190/GA/014	14
1190/GA/005	5	1190/GA/016	16
1190/GA/006	6	1190/GA/018	18
1190/GA/008	8	1190/GA/020	20
1190/GA/010	10	1190/GA/022	22
1190/GA/012	12	1190/GA/025	25



Galvanised Round Thimbles

Galvanised	Outside Diameter	Inside Diameter	Score
1160/GA/039	1½" 39mm	1" 24mm	⅝" 14mm
1160/GA/045	1¾" 45mm	1⅜" 30mm	⅝" 15mm
1160/GA/050	2" 50mm	1⅞" 35mm	⅞" 17mm
1160/GA/065	2½" 64mm	1¾" 45mm	⅞" 22mm
1160/GA/080	3⅝" 80mm	2" 52mm	1" 25mm