

Rigging & Sail Handling

Davey Ash Blocks

Inspired by our 1928 range, we have carefully developed these blocks to have the right proportions for the efficient use with ropes from 10mm to 14mm. They are strong, simple and functional but at the same time have the beauty and elegance to enhance the finest of craft.

Key Features

• Bindings: Heavy gauge stainless steel - internal. Fixed and swivel head.

• Sheaves: Tufnol type material as standard, aluminium bronze as an option.

• Bearings: Plain on oversized SS spindles to spread the load and ensure smooth running.

• Shell: High quality ash, formed into a smooth oval shape and varnished.

• Maintenance: By removing just one machine screw the block can easily be disassembled for

inspection and maintenance without damaging the wooden shell.

• Appearance: Just beautiful!



Single Block							
	Shell	Rope Size	Sheave size	SWL			
	Length	mm	mm	Kg			
0610/AH/075	3" 75mm	8 - 10	40	1500			
0610/AH/088	3 ¹ / _{2"} 88mm	10 - 12	50	1750			
0610/AH/100	4" 100mm	12 - 14	60	2000			

Single Block & Becket						
	Shell	Rope Size mm	Sheave size mm	SWL Kg		
	Length					
0611/AH/075	3" 75mm	8 - 10	40	1500		
0611/AH/088	3 ¹ / _{2"} 88mm	10 - 12	50	1750		
0611/AH/100	4" 100mm	12 - 14	60	2000		

Double Block							
	Shell	Rope Size	Sheave size	SWL			
	Length	mm	mm	Kg			
0612/AH/075	3" 75mm	8 - 10	40	1500			
0612/AH/088	3 ¹ / _{2"} 88mm	10 - 12	50	1750			
0612/AH/100	4" 100mm	12 - 14	60	2200			

Double Block & Becket						
	Shell	Rope Size	Sheave size	SWL		
	Length	mm	mm	Kg		
0613/AH/075	3" 75mm	8 - 10	40	1500		
0613/AH/088	3 ¹ / _{2"} 88mm	10 - 12	50	1750		
0613/AH/100	4" 100mm	12 - 14	60	2200		

Fiddle Block							
		Shell	Rope Size	Sheave size	SWL		
	Length		mm	mm	Kg		
0614/AH/175	7"	175mm	10 - 12	68 & 40	1750		
0614/AH/206	8	206mm	12 - 14	80 & 48	2000		

Fiddle Block & Becket							
	Shell		Rope Size	Sheave size	SWL		
	Length		mm	mm	Kg		
0615/AH/175	7"	175mm	10 - 12	68 & 40	1750		
0615/AH/206	8,,	206mm	12 - 14	80 & 48	2000		