

Door, Hatch & Interior Fittings

Hatch, Skylight & Window Stays

From this group of products it should be possible to select a fitting that will support any kind of opening flap on the boat, be it horizontal, vertical or something in between.



Bar Type Quadrants

These bar quadrants are available in two sizes in brass or chrome plated finish. The smaller size has a wing nut to lock it in place whilst the larger one has a wheel and three notches.

| | Brass | Chrome | Length | | Approx. Travel | |
|---|-------------|-------------|--------|-------|----------------|-------|
| | 8749/BR/178 | 8749/CP/178 | 7½" | 190mm | 51/2" | 140mm |
| Γ | 8749/BR/294 | 8749/CP/294 | 12" | 300mm | 9" | 230mm |

8746 8747 8743

Skylight Lifters

All of these lifts are manufactured from brass and supplied in a polished finish. The small 8746 lifter has a self-locking bracket to secure it, whereas the other two are heavy duty lifts utilising a tee bar screw.

| Brass | Length | | Approx. Travel | |
|-------------|--------|-------|----------------|-------|
| 8746/BR/190 | 7½" | 190mm | 6½" | 165mm |
| 8746/BR/250 | 10" | 250mm | 8½" | 216mm |
| 8747/BR/350 | 16" | 400mm | 14½" | 368mm |
| 8747/BR/525 | 21½" | 545mm | 19" | 483mm |
| 8743/BR/250 | 10" | 250mm | 8" | 200mm |
| 8743/BR/350 | 14" | 350mm | 12" | 300mm |



Telescopic & Slide Stays

Manufactured in brass and also available chrome plated. Both sizes of 8748 are tubular with the miniature version having a twist lock collar and the larger pattern a wheel lock. The 1209 has a sprung loaded ball bearing which locates in the fully extended position and applies friction on the flat bar at intermediate points.

| Brass | Chrome | Min & Max Length | | |
|-------------|-------------|------------------|-------------|--|
| 8748/BR/MIN | 8748/CP/MIN | 93/4" - 151/2" | 247 - 396mm | |
| 8748/BR/287 | 8748/CP/287 | 11¾" - 19¾" | 300 - 505mm | |
| 8748/BR/353 | 8748/CP/353 | 14½" - 25½" | 368 - 645mm | |
| 1209/BR | 1209/CP | 11/8" - 81/2" | 28 - 220mm | |



Hatch Slides

Our ³/₄" brass tracks, **1296/BR/T/19** & **1321/BR/T/19**, mate perfectly together to provide secure, smooth running hatch sliding gear. Supplied in 10 foot (3 metre) lengths. See page 33 for details.