

BoatCraft Pacific

MATERIAL SAFETY DATA SHEET

SECTION 1. PRODUCT IDENTIFICATION

| | | | |
|-----------------------------|---|------------------|-----|
| Trade name | AQUACOTE HIGH BUILD EPOXY UNDERCOAT | | |
| Chemical Name & Synonyms | Epoxy resin / amine hardener two component paint | | |
| Manufacturer | BoatCraft Pacific Pty. Ltd. 46 Chetwynd St Loganholme, Queensland 4129 Australia | | |
| Emergency Contact Telephone | 07 3806 1944, (ah) 07 3299 1468 | | |
| UN No. | None allocated | Hazchem | N/A |
| DG Class | None allocated | Poisons Schedule | 5 |
| CAS No. | Mixture | Pkge Grp | III |
| Intended usage | A general purpose epoxy paint packaged as two separate components | | |

Classified as hazardous according to the criteria of Worksafe Australia

SECTION 2. INGREDIENTS

| | | |
|---------------------------------|--------------------|-----------|
| Epoxy resin | CAS No. 25068-38-6 | 30 - 35 % |
| Aliphatic amine adducts | CAS No. 26950-63-0 | 10 - 15 % |
| Amidoamine | CAS No. 112-57-2 | 5 - 10 % |
| Hydrated Calcium Sulphate | CAS No. 13397-24-5 | 25 - 30% |
| Titanium dioxide pigment | CAS 13463-67-6 | 5 - 10% |
| Ethylene glycol monobutyl ether | CAS No. 111-76-2 | 2 - 5 % |
| Water | | Balance |

SECTION 3. PHYSICAL & EXPOSURE DATA

Physical data

| | |
|----------------------------|----------------------------------|
| Appearance / odour | Viscous liquids, low amine odour |
| Boiling range | 100 Deg C |
| Flash Point | 85 Deg C |
| Specific gravity | 1.12 |
| Vapour pressure | Low at 20 deg C |
| Vapour density (air = 1) | > 1 at 20 deg C |
| Volatile component (% vol) | 0 % |
| pH | 11 - 13 |
| Solubility with water | Miscible |
| Explosive limits | N/A |

Product Exposure Limits

| | |
|-----------------------|----------------------------|
| TLV TWA epoxy resin | No value assigned by NHMRC |
| TLV TWA amidoamine | No value assigned by NHMRC |
| TLV TWA amine adducts | No value assigned by NHMRC |

BoatCraft Pacific

Toxicity and Irritation Data

| | |
|--|------------|
| LD(50) for ingestion (rat) – epoxy resin | 5 gm/kg |
| LD(50) for ingestion (rat) – amines | 3.5 gm/kg |
| LD(50) for ingestion (rat) – EGMBE | 0.45 gm/kg |

SECTION 4. HEALTH HAZARD

Symptoms of Exposure: Acute and Chronic Effects

Ingestion:

Strong burning sensation, possible vomiting. Can result in irritation of the gastrointestinal tract and mucous membranes. Considered as an unlikely route of entry in commercial/industrial environments.

Eye contact:

The amine hardener component may be severely irritating to the eyes and may burn eye tissue. High concentrations of vapour may cause irritation.

Skin contact:

Liquid may be irritating to the skin and may be capable of causing allergic skin reactions. Repeated or prolonged contact may lead to dermatitic effects and may cause sensitisation in some individuals.

Inhalation:

The vapour is mildly irritating to the mucous membranes and respiratory tract. The vapour pressure from these products is very low at ambient temperatures and is unlikely to cause exposure from normal handling. Frequent or prolonged exposure can cause respiratory irritation and may cause sensitisation in some individuals. Overexposure symptoms include headache, swelling and congestion of the eyes and sinuses.

Systemic and other effects:

The ingredients may cause adverse effects including sensitisation. Symptoms include itching rash and respiratory congestion.

Emergency & First Aid Procedures

Ingestion:

DO NOT INDUCE VOMITING. If conscious give water or milk to rinse out mouth and drink. Provide liquid slowly but as much as casualty will drink. Transport to hospital or doctor without delay. Activated charcoal may be helpful.

Eye contact:

Immediately hold the eyes open and irrigate eyes with running water for at least 15 minutes. Ensure irrigation under eyelids by occasionally lifting the upper and lower lids. Transport to doctor or hospital without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin contact:

Immediately remove all contaminated clothing including footwear. Wash affected areas thoroughly with detergent hand cleaner and rinse with plenty of water. Seek medical attention in event of irritation.

BoatCraft Pacific

Inhalation:

Remove to fresh air, lie patient down, keep warm and rested. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation. Administer oxygen. Transport to hospital or doctor.

Notes to physician: Treat symptomatically.

SECTION 5. PERSONAL PROTECTION & HANDLING

Protective Equipment

Eyes: Goggles or face shield
Hands/feet: Rubber gloves, full overalls, safety shoes
Respiratory: Ensure adequate ventilation. Wear organic vapour respirator or self contained breathing apparatus in enclosed areas.
Remove and wash all contaminated clothing and equipment.

Handling Procedures

Handle in well ventilated area. Always observe conditions of good industrial hygiene and safe working practice.

SECTION 6. FIRE & EXPLOSION

Stability

Stable for minimum 2 years at room temperature. Excess heating over long periods will degrade ingredients. .

Flammability

Products will support combustion if heated but will not spontaneously ignite or explode.

Hazardous Decomposition Products

On burning will emit toxic fumes of oxides of nitrogen, carbon monoxide and carbon dioxide.

Hazardous Polymerisation

Will not occur in absence of contact with reactive elements or unless the separately packed components are mixed in large quantities. This will cause irreversible polymerization with considerable heat build-up.

Incompatibility

Avoid contact with water, strong acids, alkalis, oxidising materials.

Fire Fighting

Toxic fumes will be evolved when this material is involved in a fire. Fire fighters must wear full protective clothing and self contained breathing apparatus.

Extinguishing Media

Foam, carbon dioxide, dry chemical powder.

BoatCraft Pacific

SECTION 7. STORAGE & TRANSPORT

| | |
|-------------------------|--|
| DG Class | Non hazardous |
| Packaging Group & Label | III |
| Suitable Containers | Pre-packaged |
| Storage Procedures | Containers will develop pressure at high temperatures. Store at room temperature under cover in accordance with AS1940 and State Poisons Acts. |
| Transport | Not regulated for transport under UN and local regulations. |

SECTION 8. SPILLS & DISPOSAL

| | |
|-------------|---|
| Minor spill | Absorb into waste cloth or other suitable absorbent. Avoid contact with skin or eyes. |
| Major spill | Contain with sand or earth, absorb with suitable absorbent, collect and seal in properly labelled drums for disposal. Prevent run-off into drains or waterways. |
| Disposal | Suitable for incineration by approved agent or bury in approved landfill according to local regulations. |

SECTION 9. AUTHORISATION

| | |
|------------|--------------------|
| Name: | B.H. McConkey |
| Title | Technical Director |
| Issue Date | |